

## evvoli Gas Boiler

Model name	EVGB-CM26
Balance Exhaust type	√
Rated heating input	26
Minmum heating input	8.9
Rated heating output	23.1
Minmum heating output	8
Heating temperature regulation range	30-80
Floor heating temperature regulation range	30-60
Applicable water pressure of the heating system	0.04-0.3
Maximum pressure of the heating system	0.3
Capacity of the expansion tank	6
Pre-charge pressure of the expansion tank	0.1
Temperature regulation of the sanitary hot water	35-60
Maximum pressure of the sanitary hot water	0.8
Minimum pressure of the sanitary hot water	0.02
Δt=25K nominal hot water production rate	13.2
Δt=30K nominal hot water production rate	11
Rated Voltage / Freq	220V/50Hz
Maximum input electric power	110 W
Insulation grade	Grade I
Waterproofing grade	IPX4D
Heating water outlet/bacakwater interface	G3/4
Sanitary hot water/cole water interface	G1/2
Gas interface	G3/4
Cold inlet water	G1/2
Hot outlet water	G1/2
Flue pipe / Chimney diameter	φ60/φ100
Efficiency	89%
Net Weight (kg)	30
Gross Weight (kg)	33.0
Product dimensions (mm)	700*420*240
Packaging dimensions (mm)	835*503*322
Loading Qty (pcs)	
20GP	210
40GP	420
40HQ	480
40HQ(Loaded with flue pipe)	394