Evvoli name		EVWD-KS1500
Product Type		Bottle
		Hot & Cold
Voltage - Frequency		220V ~ 240V 50Hz
Cooling System	Power Consumption (Cold)	105W
	Cold Tank Capacity	3.2 liters
	Temperature	4 ~ 10°C
	Cooling System	Compressor
	Temperature Control	Thermostat
Heating System	Heating System	Sheath Heater
	Power Consumption (Hot)	440W
	Hot Tank Capacity	2 liters
	Temperature	85 ~ 90°C
	Temperature Control	Automatic + Manual Bimetal
Compressor (Country of origin)		LG Compressor (Made in Korea)
Refrigerant Type		R-134a
Water Pipe Materials		STS304
Safety devices		Overheating Protection + PTC
FEATURES		
LED Display Panel		•
Water Outlet Control (Push)		•
Water Outlet (2 Taps)		•
Hot Water Child Lock		•
Hot & Cold STS 304 Water Pipe		•
Direct Drain Available		•
Optical sensor ECO System		-
UV LED Sterilization System		-
DIMS & WEIGHTS		
Unit Weight (kg)		17 kg
Unit Dimensions (W x D x H) mm		300 x 320 x 1125
CNTR Loading Q'ty (Unit)		
20ft		230 unit
40HC		478 unit
	÷	

evvoli Water Dispenser